

Owner's Manual & Safety Instructions


Save This Manual Keep this manual for the safety warnings and precautions, assembly, operating, inspection, maintenance and cleaning procedures. Write the product's serial number in the back of the manual near the assembly diagram (or month and year of purchase if product has no number). Keep this manual and the receipt in a safe and dry place for future reference.

21k

Bauer™

20201L-B

100 FT SELF-LEVELING 3-DOT LASER LEVEL



Visit our website at: <http://www.harborfreight.com>
Email our technical support at: productsupport@harborfreight.com

57528

When unpacking, make sure that the product is intact and undamaged. If any parts are missing or broken, please call 1-888-866-5797 as soon as possible.

Copyright © 2020 by Harbor Freight Tools®. All rights reserved.
No portion of this manual or any artwork contained herein may be reproduced in any shape or form without the express written consent of Harbor Freight Tools. Diagrams within this manual may not be drawn proportionally. Due to continuing improvements, actual product may differ slightly from the product described herein. Tools required for assembly and service may not be included.

⚠ WARNING

Read this material before using this product. Failure to do so can result in serious injury. **SAVE THIS MANUAL.**

Table of Contents

Safety	2	Operation	5
Specifications	3	Maintenance	7
Setup	4	Warranty	8

Bauer™

WARNING SYMBOLS AND DEFINITIONS

	This is the safety alert symbol. It is used to alert you to potential personal injury hazards. Obey all safety messages that follow this symbol to avoid possible injury or death.
	Indicates a hazardous situation which, if not avoided, will result in death or serious injury.
	Indicates a hazardous situation which, if not avoided, could result in death or serious injury.
	Indicates a hazardous situation which, if not avoided, could result in minor or moderate injury.
	Addresses practices not related to personal injury.

IMPORTANT SAFETY INFORMATION

Safety Warnings and Precautions

WARNING

Read all safety warnings and all instructions.

Failure to follow the warnings and instructions may result in electric shock, fire and/or serious injury.

Save all warnings and instructions for future reference.

1. Never attach or use any other form of optical device with this product. Use as intended only.
2. Do not modify in any way as this may result in hazardous radiation exposure.
3. This product is not a toy. Do not allow children to play with or near this item.
4. Inspect before every use; do not use if parts are loose or damaged.
5. Laser beams emit from all three Laser Apertures.
6. Power this Laser Level using only the batteries referenced in the Specifications Chart.
7. Stay alert. Watch what you are doing, use common sense. Do not operate any Laser Level when you are tired.
8. Do not operate Laser Level if under the influence of alcohol or drugs. Read warning labels on prescriptions to determine if your judgment or reflexes are impaired while taking drugs. If there is any doubt, do not operate the Laser Level.

8. Do not look into laser. Do not point laser at persons or animals directly or indirectly off of reflective surfaces.
9. Avoid damaging Laser Level. Use only as specified in this manual.
10. Performance of this Laser Level may vary depending on battery condition.
11. Turn Laser Level's Self-Leveling Switch to the "OFF" position before making any adjustments or changing the batteries.
12. The Laser Level is a delicate instrument; do not drop or jar the Laser Level.
13. Maintain product labels and nameplates. These carry important safety information. If unreadable or missing, contact Harbor Freight Tools for a replacement.
14. Do not attempt to charge batteries.
15. Do not install old and new batteries together. Do not install alkaline, carbon-zinc or rechargeable batteries together. Position batteries in proper polarity. Do not use swollen or leaking batteries.
16. Have the Laser Level calibrated by a qualified technician every year to maintain accurate results.
17. People with pacemakers should consult their physician(s) before use. Electromagnetic fields in close proximity to heart pacemaker could cause pacemaker interference or pacemaker failure.
18. The warnings, cautions, and instructions discussed in this instruction manual cannot cover all possible conditions and situations that may occur. It must be understood by the operator that common sense and caution are factors which cannot be built into this product, but must be supplied by the operator.



SAVE THESE INSTRUCTIONS.

Specifications

Working Range	Up to 100 ft (30.48 meters)
Accuracy	$\pm 0.5\text{mm/m}$ ($\pm 3/16"$ @ 33 ft)
Tripod Connector	1/4" - 20
Battery	2x AA (Included)
Self-Leveling Time	5 seconds
Self-Leveling Range	$\pm 3^\circ$ of the horizontal plane
Working and Storage Temperature	32°F - 104°F (0°C - 40°C)
Operating Environment	Indoors





Setup - Before Use:



Read the **ENTIRE IMPORTANT SAFETY INFORMATION** section at the beginning of this manual including all text under subheadings therein before set up or use of this product.

Functions



Operating Instructions





Read the **ENTIRE IMPORTANT SAFETY INFORMATION** section at the beginning of this manual including all text under subheadings therein before set up or use of this product.

Mounting (Optional)

The Level can be mounted onto a Tripod (sold separately) or attached to a Mounting Bracket (included).

1. Attach to Tripod's connecting screw.
2. To attach the Mounting Bracket, insert the Bracket's Screw into the Laser Level's Tripod Connector. Turn Knob to tighten until secure.
 - a. Attach the Mounting Bracket to a magnetic surface, or
 - b. The Bracket may be attached to a wall using appropriate hardware (sold separately) through its two holes.



Bauer™

General Operation

NOTICE: Turn Self-Leveling Switch OFF when moving Level to a different location.

1. Install batteries as described in "Battery Replacement" on page 7.

2. Set the Level on a flat, level surface, mount to Tripod or Mounting Bracket.

Self Leveling

1. Turn the Self-Leveling Switch ON.
 - a. The Level will self-level within 5 seconds and the Leveling Indicator will illuminate green.
 - b. Three laser lines (front, up, down) will emit from the Level to check plumb and level.

Note: If the Level is out of alignment, the Leveling Indicator will illuminate red and the laser lines will blink. Move the Level horizontally until Leveling Indicator illuminates green.

2. Aim and tilt the Level as needed.

Note: Tilting Level up and down may cause it to become out of alignment. Move the Level horizontally until Leveling Indicator illuminates green.

3. When finished, turn the Laser Button and Self-Leveling Switch OFF. Store the Level in a dry indoor area away from children. If storing the Level for a long period, remove the batteries.

Maintenance and Servicing



Procedures not specifically explained in this manual must be performed only by a qualified technician.


Cleaning, Maintenance, and Lubrication

1. Wipe unit with a dry, lint-free cloth. Do not use solvents or abrasives.
2. Remove batteries if not in use for long periods.
3. Store unit in a dry location.
4. Other than the batteries, there are no replaceable parts on this unit. **Repairs should be done by a qualified technician.**

Battery Replacement

1. Turn the Self-Leveling Switch and Laser Button Off.
2. Remove battery cover by pressing the Latch and removing the cover.
3. Remove batteries. Replace with two new AA batteries and follow polarity.
4. Replace battery cover and be sure the Latch connects securely.

Note: Do not install old and new batteries together. Do not install alkaline, carbon-zinc or rechargeable batteries together. Position batteries in proper polarity. Do not use swollen or leaking batteries.



Calibration

Have the Laser Level calibrated by a qualified technician every year.

Record Serial Number Here:

Note: If product has no serial number, record month and year of purchase instead.

Note: Replacement parts are not available for this item.
Reference UPC 193175416872.

Limited 90 Day Warranty

Harbor Freight Tools Co. makes every effort to assure that its products meet high quality and durability standards, and warrants to the original purchaser that this product is free from defects in materials and workmanship for the period of 90 days from the date of purchase. This warranty does not apply to damage due directly or indirectly, to misuse, abuse, negligence or accidents, repairs or alterations outside our facilities, criminal activity, improper installation, normal wear and tear, or to lack of maintenance. We shall in no event be liable for death, injuries to persons or property, or for incidental, contingent, special or consequential damages arising from the use of our product. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation of exclusion may not apply to you. THIS WARRANTY IS EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS.

To take advantage of this warranty, the product or part must be returned to us with transportation charges prepaid. Proof of purchase date and an explanation of the complaint must accompany the merchandise. If our inspection verifies the defect, we will either repair or replace the product at our election or we may elect to refund the purchase price if we cannot readily and quickly provide you with a replacement. We will return repaired products at our expense, but if we determine there is no defect, or that the defect resulted from causes not within the scope of our warranty, then you must bear the cost of returning the product.

This warranty gives you specific legal rights and you may also have other rights which vary from state to state.

The logo for Bauer, featuring the word "Bauer" in a bold, italicized, sans-serif font. The letters are black with a white outline, and a small trademark symbol (TM) is located at the bottom right of the word.

26677 Agoura Road • Calabasas, CA 91302 • 1-888-866-5797

