



**HAYWARD®**

## **XStream® Series**

»»» Above-Ground Filter Systems

**HIGH-CAPACITY SIZE FOR  
HIGH-QUALITY FILTRATION**



# XSTREAM® SERIES ABOVE-GROUND FILTER SYSTEM FEATURES

- » **Extra-large filter body** holds more dirt and debris and allows for more even distribution of particles throughout the filter cartridge, reducing maintenance and extending the filtration cycle
- » **Quick-release, high-capacity air relief valve** provides easy release of extra air for hassle-free filter operation
- » **Glass-reinforced, noncorrosive filter tank** provides all-weather durability
- » **Easy-Lok™ ring design** offers single-turn access to internal components
- » **Quick-connect unions** install with flexible or rigid plumbing
- » **One-piece base** provides safe, stable support



## CC1000 ADDITIONAL FEATURES

- » 80 GPM flow rate
- » 100 ft<sup>2</sup> cartridge elements
- » PowerFlo Matrix® or PowerFlo® LX pump options



## CC1500 ADDITIONAL FEATURES

- » 120 GPM flow rate
- » 150 ft<sup>2</sup> cartridge elements
- » PowerFlo Matrix or PowerFlo LX pump options

## SPECIFICATIONS

|                |                                                                                 |
|----------------|---------------------------------------------------------------------------------|
| Filter Type    | Full-flow cartridge element                                                     |
| Filter Tank    | Injection-molded glass reinforced                                               |
| Filter Element | 360° self-cleaning slotted laterals, precision installed in ball-joint assembly |
| Fastenings     | Easy-Lok ring assembly                                                          |
| Mounting Base  | Injection-molded glass reinforced                                               |

## FILTER PERFORMANCE DATA

| FILTER NUMBER                  | EFFECTIVE FILTRATION AREA | DESIGN FLOW RATE | PRESSURE LOSS (AT DESIGN FLOW RATE) | MAXIMUM WORKING PRESSURE |            |
|--------------------------------|---------------------------|------------------|-------------------------------------|--------------------------|------------|
| CC1000                         | 100 ft. <sup>2</sup>      | 80 GPM           | 1 psi                               | 35 psi                   |            |
| CC1500                         | 150 ft. <sup>2</sup>      | 120 GPM          | 1 psi                               | 35 psi                   |            |
| REPLACEMENT HAYWARD® CARTRIDGE | REQUIRED CLEARANCE        |                  | TURNOVER                            |                          |            |
|                                | SIDE                      | ABOVE            | 8 HOURS                             | 12 HOURS                 |            |
|                                | CCX1000RE                 | 18"              | 24"                                 | 38,400 gal               | 57,600 gal |
|                                | CCX1500RE                 | 18"              | 30"                                 | 57,600 gal               | 86,400 gal |

» [hayward.com](http://hayward.com) » 1-888-HAYWARD

XStream Filters are listed by (when provided with a 3-foot twist-lock cord):



Pumps » Filters » Heating » Cleaners » Sanitization » Automation » Lighting » Water Effects » White Goods

Hayward, PowerFlo, PowerFlo Matrix and XStream are registered trademarks and Easy-Lok is a trademark of Hayward Industries, Inc. © 2017 Hayward Industries, Inc. All other trademarks not owned by Hayward are the property of their respective owners. Hayward is not in any way affiliated with or endorsed by those third parties.



LITXSABG17

