


**CROSBY ELIMINATOR®****WARNING & APPLICATION INSTRUCTIONS****⚠ WARNING**

- Failure to read, understand, and follow these instructions may cause death or serious injury.
- Read and understand these instructions before using the Crosby ELIMINATOR®.
- Incorrectly rigging or terminating exerts additional force or loading, which the Crosby ELIMINATOR® is not designed to accommodate.

**Crosby ELIMINATOR® Definitions**

The Crosby ELIMINATOR® consists of a bail, hinge bolt, latch pin, and lower body with cradle slot/slots.




The Crosby ELIMINATOR® incorporates markings forged into the product which address a **QUIC-CHECK®** feature:








**Deformation Indicators** – Two strategically placed marks on each leg of the bail, which allows for a **QUIC-CHECK®** measurement to determine if the bail opening has changed, thus indicating abuse or overload. To check, use a measuring device (i.e. tape measure) to measure the distance between the marks. The marks should align to either an inch or half-inch increment on the measuring device. If the measurement does not meet criteria, the Crosby ELIMINATOR® bail should be inspected further for possible damage.

**Important Safety Information  
Read and Follow**

- A visual periodic inspection for cracks, nicks wear, gouges and deformation as part of a comprehensive documented inspection program, should be conducted by trained personnel in compliance with ANSI B30.9.
- Remove from service any Crosby ELIMINATOR® components with a crack, nick, or gouge. The bail and body of a Crosby ELIMINATOR® with nick or gouge shall be repaired by a qualified person. The qualified person shall repair by grinding longitudinally following the contour of the forging, provided that the reduced dimension is within the limits shown in (Fig. A).

**Figure A**

- Never repair, alter, rework, or reshape a Crosby ELIMINATOR® by welding, heating, burning, or bending.
- Crosby ELIMINATOR® combination master link and chain shortener shall not be used in a manner other than that for which it is intended.
- The sling may be shortened by use of the cradle slot/slots (see Fig. C).
- In shortening applications, the Crosby ELIMINATOR® can be used without any reduction to the Working Load Limit.
- Never terminate (i.e. place a load bearing chain sling hook), or reeve load bearing chain through Crosby ELIMINATOR® bail (see Fig. B).
- Never exceed the rated capacity shown on sling's identification tag.
- Attach lifting device to ensure free fit of Crosby ELIMINATOR® bail (see Fig. D). Never allow lifting device to apply forces on side of bail (see Fig. E), as this condition will damage and reduce the capacity of the Crosby ELIMINATOR®.
- The Crosby ELIMINATOR® is intended for tension or pull. Side loading must be avoided, as it exerts additional force or loading which the product is not designed to accommodate (see Fig. F).

**Figure B****Figure C****Figure D****Figure E****Figure F**

- Never use a Crosby ELIMINATOR® where the bail shows signs of deformation or overloading (see Table 1).
- Read and understand the other sections of the ALLOY STEEL CHAIN SLINGS Warning, Selection, Use & Maintenance Information.

| TABLE 1<br>Crosby ELIMINATOR® Bail Dimensions |                    |      |                       |                      |                   |                         |
|-----------------------------------------------|--------------------|------|-----------------------|----------------------|-------------------|-------------------------|
| Chain Size<br>(in)                            | Frame I.D.<br>(mm) | Code | Inside Length<br>(in) | Inside Width<br>(in) | Jaw Width<br>(in) | QUIC-CHECK® Dim<br>(in) |
| 1/4 - 5/16                                    | 7 - 8              | 2    | 3.88                  | 3.00                 | .94               | 3.50                    |
| 3/8                                           | 10                 | 3    | 4.81                  | 3.50                 | 1.13              | 4.00                    |
| 1/2                                           | 13                 | 4    | 6.00                  | 4.13                 | 1.31              | 5.00                    |
| 5/8                                           | 16                 | 5    | 6.88                  | 4.75                 | 1.63              | 6.00                    |

- A Crosby ELIMINATOR® under load shall be allowed to self-align itself about the hinge pin.
- The use of a latch may be mandatory by regulations or safety codes; e.g. OSHA, MSHA, ASME B30.10 and B30.9.
- If Crosby latch pin is present, it should fit and function properly, and show no signs of distortion or bending.
- Always make sure the chain is seated in the cradle slot, and the cradle supports the load. The latch pin must never support the load.
- Latch pins are not intended to be an anti-fouling device.
- Use only genuine Crosby repair and latch pins parts.