

MARMITEK®

Subwoofer Anywhere 640

Connect your subwoofer wirelessly



Package content

- 1x Transmitter
- 1x Receiver
- 2x Type C power cable
- 2x Stereo RCA to RCA cable
- 2x Shielded subwoofer cable
- 2x 5V USB-A Power adapter
- 1x Quick guide



Audio



Multi language user guide



Safety instructions

Please read these instructions thoroughly before you use the device and keep them for future reference.

- Only for indoor use.
- Do not expose the product to extremely high or low temperatures, strong light sources or direct sunlight.
- This product is not a toy. Keep out of reach of children.
- Connect the adapter to the mains only after you have verified that the line voltage corresponds to the value specified on the type plates.
- Never connect a power adapter if it's damaged. In such cases, please contact your supplier.
- Disconnect the AC/DC power adapter from the mains when this device is not in use for prolonged time.
- Never open the product: the device may contain parts with deadly voltage.
- Repairs or service should only be performed by qualified personnel.

Installation

- We recommend that you switch off your equipment before connecting cables in order to prevent any of the devices being damaged.
1. Use the supplied audio cable to connect the Subwoofer Anywhere 640 transmitter to the subwoofer output of your audio system.
 2. Use the supplied audio cable to connect the Subwoofer Anywhere 640 receiver to the LFE/LINE IN connection on your Active Subwoofer.
 3. Connect the power adapters [3] with the USB C cable to the Transmitter and Receiver and plug the power adapters into the electrical socket.
 4. The Transmitter and Receiver will automatically turn on and the white LED will flash slowly. On connection the LED light will be steady.
 5. The audio connection is ready to use.

Declaration of Conformity



Hereby, Marmitek BV, declares that this Subwoofer Anywhere 640 set is in compliance with the essential requirements of the 2014/53/EU, 2011/65/EU and 2009/125/EC: 2019/1782 Directives.

Full Declaration of Conformity is available at www.marmitek.com/en/declarations-of-conformity/

More detailed user guide and instructions are available on our website at www.marmitek.com

Pairing

When you want to pair an extra receiver, push the power button 2 times quickly on the transmitter. The LED light will flash quickly. Do the same on the new receiver. After a few seconds the LED light will light up steady and the new receiver is operational.

Standby

When there is no audio input for more than 30 minutes, the Subwoofer Anywhere 640 set will go in standby and the LED light will turn off. When audio input is detected again, the set will wake up in a few seconds and the wireless audio connection will work again.

Power off

Long press the power button to turn off the transmitter and or receiver.

Frequently asked questions (FAQs)

Please go to www.marmitek.com if you have any questions.

Technical specifications

Audio transfer method	Digital
Transmitter frequency	2.4 GHz
Frequency channels	26 channels
RF connection	Paired connection (TX and RX)
Extra receivers	up to 10 extra RX
Supported audio freq.	20 Hz ~ 20 kHz
Audio delay	12.5 ms (between TX and RX)
Audio input/output	2x RCA (Stereo L/R + sub)
Operating range	Up to 100 meters clear field, up to 20 meters through walls and ceilings.
Data transfer speed	Up to 2 Mbps, GFSK modulation
Standby	After 30 minutes no audio
Power	5 VDC USB adapter with USB Type C cable
Power consumption	0.9 W (transmitter) and 0.3 W (receiver)
Standby (auto)	<0.25 W (TX/RX)
Standby (power button)	< 0.15W (TX) and < 0.1W (RX)
Dimensions (h x w x d)	90*75*22mm (TX/RX)
Weight	160 grams



audio

20689/20220712 | Subwoofer Anywhere 640
all rights reserved © MARMITEK

stay connected

marmitek.com

