


70mai Rear Camera User Manual

70迈高清后录摄像头使用说明书

70mai

Product Overview

Please read this manual carefully before using the product and keep it in a safe place.



- ① Rear Camera
- ② Mount
- ③ Rear Camera Lead Wire
- ④ Joint (Port A)
- ⑤ Joint (Port B)
- ⑥ Rear Signal Wire
- ⑦ Mini USB 8PIN Power Port

Note: Illustrations of the product, accessories, and user interface in the user manual are for reference purposes only. The actual product and functions may vary due to product enhancements.

Functions

The 70mai rear camera is used as an accessory for 70mai in-car products and needs to be used with a main device.

After the rear camera is installed and connected with the main device correctly, when rear camera recording is enabled, the rear camera can record and store the image from the rear of the vehicle.

Usage

- The 70mai rear camera is powered by the main device. When the main device starts operation, the rear camera will also be turned on auto-


matically. When the main device is turned off or sleeps, the rear camera will also be turned off automatically.

- The main device powers the rear camera only when the main device receives power from an external power source. The main device cannot power the rear camera if it is not powered by the external power source.
- The image acquired by the rear camera is stored in the microSD card of the main device automatically. As the storage limit is reached for the microSD card, the earliest front-recorded and rear-recorded images will be overwritten by the latest images and deleted in turn cyclically.

Installation


1. Installing the electrostatic sticker.

Clean your rear windshield and put the electrostatic sticker on the recommended upper area of the windshield, as shown in the figure below. Make sure you remove air bubbles between the sticker and the glass.



2. Installing the rear camera.


Peel off the protective film from the adhesive sticker on the base of the mount, and paste the rear camera onto the electrostatic sticker in the dotted area.



3. Connecting the power supply.


Connect the rear camera with the rear signal wire (connect ports A and B together).

As shown in the figure below, run the wire along the top of the rear windshield, C-pillar, top of the side windows to the main device. Plug the Mini USB 8PIN power port into the main device (the AV/IN port of the main device).



4. Adjusting the dash cam angle.

Turn on the main device and switch to rear camera recording mode. Adjust the camera angle based on the preview screen to ensure that the camera is facing the back of the vehicle.



Note: The installation and wiring methods for different vehicles may differ from what described in the user manual. The installation shall be conducted by a professional installer.

Online Guide

Scan the below QR code to access the online guide. The guide provides detailed product information including descriptions of functions. Please carefully read this guide before use in order to avoid damage due to incorrect use.



Precautions

1. Please employ a professional installer for installation. The Company shall not be liable for improper personal operation that causes issues such as short circuit of car power source, damage to the car battery, damage to the car interior, and the like.
2. The Company shall not be liable for damages due to installation, rather than quality issue of the product itself.
3. The Company shall not be liable for failed normal use of this product that is not resulted from quality issue of this product.
4. During installation and use of the product, please do not insert or remove the rear camera while the power is on, otherwise the product may be damaged.

Specifications

Model: Midrive RC06

Input: 5V $\pm$ 0.5A

Resolution: 1920×1080

Packing list

70mai Rear Camera ×1

Rear Signal Wire ×1

Electrostatic Sticker × 2

Adhesive Sticker × 2(with 1 pre-applied to the mount)

User Manual ×1

Service: help@70mai.com

For further information, please go to www.70mai.com


Manufacturer: 70mai Co., Ltd.

Address: Room2220, building2, No.588, Zixingroad, MinHangDistrict, Shanghai, China

V1.0-20200628



产品介绍



使用产品前请仔细阅读本说明书，并妥善保管。

- ① 摄像头
- ② 底座
- ③ 摄像头引出线
- ④ 接头（A口）
- ⑤ 接头（B口）
- ⑥ 视频信号线
- ⑦ Mini USB 8PIN电源接口

提示：说明书中的产品、配件、用户界面等插图均为示意图，仅供参考。由于产品的更新与升级，产品实物与示意图可能略有差异，请以实物为准。

产品功能

70迈高清后录摄像头作为70迈车载产品的配件，需要与主设备一起使用。

在正确安装和连接主设备并开启后录功能后，后录摄像头可采集来自车辆后方的影像，并存储在主设备的存储卡中。

使用方法


- 70迈高清后录摄像头由主设备供电，在主设备开启运行时，摄像头也会自动开启。主设备关机或休眠时，摄像头也自动关闭。
- 主设备对摄像头的供电，仅在主设备获得外部电源供电时进行。如果主设备没有外部电源供电，无法为摄像头供电。
- 摄像头获取的影像被自动存储在主设备的存储卡中。当存储卡达到存储上限时，最新的影像将会覆盖时间最早的前录和后录影像，依次循环删除。

产品安装

1. 安装静电贴


将静电贴安装在下图所示虚线区域内的后挡风玻璃de上部区域内。

安装前请将玻璃擦拭干净，安装时请将静电贴与玻璃之间的气泡挤压干净。




2. 粘贴摄像头

撕下底座耐高温胶上的保护贴，将摄像头粘贴在静电贴的正中位置。



3. 布线并连接电源


将摄像头和视频信号线连接（A口和B口连接），将连接线沿后挡风玻璃的顶部、C柱、侧窗顶部，布置到主设备处，将Mini USB 8PIN电源接口接入主设备（主设备的AV/IN 接口）。



提示：不同车辆的安装和布线方法可能与说明书存在差别，请由专业的安装人员进行安装。

4. 调节摄像头

将主设备开机，开启后录功能，对照预览画面，上下调整摄像头的角度，确保摄像头朝向车尾正前方。



用户指南

在线指南包括详细的产品功能描述，使用本产品前，请仔细阅读本指南，避免因错误的使用造成损失。

扫描下方二维码，获取在线指南。



安装服务

请务必联系专业人员安装70迈高清后录摄像头。如需安装服务，请扫描以下二维码填写相关信息，并支付相应安装费用。



注意事项

- 1. 请由专业安装人员进行安装，如果因个人操作不当，造成汽车电源短路、汽车电瓶损坏、汽车内饰损坏等问题，本公司不承担责任。
- 2. 由于安装原因，而非产品本身质量问题造成的损失，本公司不承担责任。
- 3. 非本产品质量问题导致的本产品无法正常使用，本公司不承担责任。
- 4. 在产品安装和使用过程中，请勿在开机状态下插拔摄像头，以免造成产品损坏。

基本参数

产品型号：Midrive RC06
输入参数：5V === 0.5A
图像分辨率：1920×1080
执行标准：Q31/0112000713C001-2018

包装清单

70迈高清后录摄像头×1
视频信号线×1
静电贴 × 2
耐高温胶 × 2（1片出厂前已粘贴在底座上）
说明书（内含三包凭证）×1

产品中有害物质的名称及含量

部件名称	有害物质					
	铅 (Pb)	汞 (Hg)	镉 (Cd)	六价铬 (Cr(VI))	多溴联苯 (PBB)	多溴二苯醚 (PBDE)
主机外壳及组件	×	○	○	○	○	○
主机内部电子组件	○	○	○	○	○	○

本表格依据SJ/T 11364的规定编制。
×：表示该有害物质至少在该部件的某一均质材料中的含量超出了GB/T 26572 规定的限量要求。
○：表示该有害物质在该部件所有均质材料中的含量均在 GB/T 26572 规定的限量要求以下。



三包凭证

1. 用户信息

姓 名：_____

电 话：_____

电子邮件：_____

邮政编码：_____

联系地址：_____

2. 维修记录

受理日期	故障现象	处理方案	维修员签字

服务政策

本公司严格依据《中华人民共和国消费者权益保护法》、《中华人民共和国产品质量法》为购买本公司产品的消费者提供三包服务。

详细的服务政策，请参考本公司官网售后服务政策栏内容：<http://www.70mai.com/service/mainland>

联系我们

官 网： www.70mai.com
电 话： 400-015-2399
制造商： 上海新案数字科技有限公司
地 址： 上海市闵行区紫星路588号2幢2220 室
扫描右侧二维码关注70迈微信公众号

