

# Integrated Warming Drawer, 30"

Series 9 | Integrated

Panel Ready



Keep plates warm until ready to serve; rapid proof or slow cook. Panel-ready, you can match it with your cabinetry.

- Integrate your warming drawer into your surrounding cabinetry for seamless design
- Space to keep 16 standard-sized place settings evenly warm, with accessory rack for optimising space
- Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

## DIMENSIONS

|        |           |
|--------|-----------|
| Height | 10 11/16" |
| Width  | 28 7/16"  |
| Depth  | 22 3/16"  |

## FEATURES & BENEFITS

- Complementary design**  
Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.
- Multi-function flexibility**  
Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.
- Easy to clean**  
Cleaning and care of the Warming Drawer is simple. After each use, just wipe out the smooth glass interior with a damp cloth.
- Easy to use**  
Soft-close with capacitive touch controls, our Warming Drawer comes with an accessory rack for optimising space.

- Precise control**  
With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking, as well as resting after a traditional roast in the oven and proofing dough.
- Safe and sound**  
With Automatic switch-off and Delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

## SPECIFICATIONS

Accessories

|                                 |                       |
|---------------------------------|-----------------------|
| Professional round flush handle | Part 82139 (optional) |
| Square fine aluminium handle    | Part 82105 (optional) |
| Square fine black handle kit    | Part 82103 (optional) |
| Wire shelf                      | 1                     |

|                          |          |
|--------------------------|----------|
| Capacity                 |          |
| Accessory rack maximum   | 42lb     |
| Cappuccino cups          | 24       |
| Espresso cups            | 54       |
| Maximum allowable weight | 55lbs    |
| Place settings           | 16       |
| Usable depth             | 16 1/16" |
| Usable height            | 9 1/16"  |
| Usable width             | 27 1/2"  |

|                              |   |
|------------------------------|---|
| Cleaning                     |   |
| Easy clean smooth-glass base | • |

|                             |                          |
|-----------------------------|--------------------------|
| Controls                    |                          |
| Audio feedback              | •                        |
| Automatic timers            | 30', 45', 1h, 2h, 4h, 6h |
| Delayed start               | •                        |
| Electronic capacitive touch | •                        |
| Pre-set heating functions   | •                        |
| Sabbath mode                | •                        |
| Soft close drawer           | •                        |
| Standby mode                | •                        |

|           |   |
|-----------|---|
| Functions |   |
| Cups      | • |



|                     |   |
|---------------------|---|
| Dehydrate           | • |
| Number of functions | 6 |
| Plates              | • |
| Rapid proof         | • |
| Slow cook           | • |
| Warm                | • |

### Performance

|                           |            |
|---------------------------|------------|
| Heated glass base and fan | •          |
| Low temperature cooking   | •          |
| Temperature levels        | 6          |
| Temperature range         | 95°F-185°F |

### Power requirements

|                  |                        |
|------------------|------------------------|
| Amperage         | 10A                    |
| Power outlet     | 3-prong grounding-type |
| Supply frequency | 60Hz                   |
| Supply voltage   | 110V                   |

### Product dimensions

|                                |           |
|--------------------------------|-----------|
| Adjustable front door panel to | •         |
| Depth                          | 22 3/16"  |
| Height                         | 10 11/16" |
| Width                          | 28 7/16"  |

### Safety

|                             |   |
|-----------------------------|---|
| Automatic turn off after 12 | • |
| Full extension slides       | • |

### Warranty

Parts and labor **2 years**

SKU 82114

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

### Other product downloads available at fisherpaykel.com

- [↓](#) User Guide
- [↓](#) Guide d'utilisation
- [↓](#) Installation Guide
- [↓](#) Data Sheet Integrated Warming Drawer



### A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 W [www.fisherpaykel.com](http://www.fisherpaykel.com)

