



User Manual

3-in-1 DisplayPort™ to HDMI® (4K), VGA, or DVI converter Adapter HDMI 4K@30Hz - PC - Black

Y10A259-B1

Congratulations

Thank you for purchasing this premium Rocstor this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or using this product. Please keep this manual for future reference.

Introduction

This is a premium Rocstor DisplayPort 1.2 to HDMI, DVI and VGA adapter, designed for connecting DP monitor to high definition monitors with HDMI, VGA and DVI monitors. It is convenient to use. With three outputs, you can choose to use one of them for one time as your practical need with corresponding cables. It offers solutions for digital entertainment center, HDTV retail and show site, HDTV, STB, DVD and Projector factory, noise space and security concerns, data center control, information distribution, conference room presentation, school and corporate training environments.

Package Contents

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the Packaging:

- Main unit x1
- User Manual x1

How to Use

- 1 - Connect the DisplayPort male port of this multiport adapter to the host computer.
- 2 - Connect the DVI port of this multiport adapter to a DVI monitor.
- 3 - Connect the HDMI port of this multiport adapter to an HDMI monitor.
- 4 - Connect the VGA port of this multiport adapter to a VGA monitor.

Features

Upstream:

DisplayPort Male (Connect to host computer)

- Supports Display Port 1.2 Dual-mode input
- DisplayPort port supports DP v1.2, which is for 1.62 Gbps, 2.7 Gbps, 5.4 Gbps link rates

Downstream:

VGA x1 Female



- Supports VGA resolution up to 1920x1200@60Hz

HDMI x1 Female



- Support HDMI highest video resolution 4Kx2K@30Hz

DVI x1 Female



- Support DVI resolution up to 1080P@60HZ

- If two or more outputs are connected, only one output port can receive input signal.
- Automatic Power Management: Enter power saving mode automatically when output display is not connected.
- Powered from DisplayPort source.

Specification

Input / Output Connector

Input	DisplayPort Male x1
Output	DVI Female x1 HDMI Female x1 VGA Female x1

Warranty

Limited Warranty	3 Year
------------------	--------

Environmental

Operating Temperature	0°C to + 45°C - (32°F to + 113°F)
Operating Humidity	10% to 80 % RH (no condensation)
Storage Temperature	-10°C to + 70°C - (14°F to + 158°F)
Storage Humidity	5% to 90 % RH (no condensation)

Power Requirement

Power Source	Powered from DP input
Power consumption	DVI output: <200mA HDMI output: <400mA VGA output: <400mA

Regulatory Approvals


Certifications	FCC, CE
----------------	---------

Mechanical

Size (L-W-H)	
Weight (Net)	

Accessories

User Manual	English Version
-------------	-----------------



Support

Technical support is available to all the registered users of Rocstor products.

Technical Support / RMA

Hours: 9:00 am - 5:00 pm PST

Monday to Friday (except holidays)

Tell: +1 (818) 727-7000 (National and international)

Fax: +1 (818) 875-0002

Email: support@Rocstor.com

⚠ Safety Information:

WARNING: Please follow these safety instructions. Failure to do so may result damages or injury. It is normal that the Rocstor Multi-port Hub adapter becomes very warm during use.

Please note that:

continuous contact with warm surfaces for extended time may cause discomfort or injury. In order to reduce the possibility of overheating or heat-related injuries, always allow needed ventilation around the Rocstor Multi-port Hub adapter and use care when handling it. Avoid instances where your skin is in extended contact with the hub when plugged into the host computer. It is not recommended to sleep with the adapter when plugged into a host computer. Avoid placing the hub adapter under a pillow, blanket, or your body when connected to a host computer. If you have a medical condition that affects your ability to detect heat against the body, extra care should be used. Never use the adapter in locations with water, such as a sink, bathtub, or shower stall. Never connect or disconnect the adapter with wet hands.



Warranty Information

Warranty Information

This product is backed by a (3) three-year warranty. Rocstor warrants its products against defects in materials and workmanship for the periods noted, following the initial date of purchase. During this period, the products may be returned for repair, or replacement with equivalent products at our discretion. The warranty covers parts and labor costs only. Rocstor does not warrant its products from defects or damages arising from misuse, abuse, alteration, or normal wear and tear.

Limitation of Liability

In no event shall the liability of Rocstorage, Inc. and Rocstor (or their officers, directors, employees or agents) for any damages (whether direct or indirect, special, punitive, incidental, consequential, or otherwise), loss of profits, loss of business, or any pecuniary loss, arising out of or related to the use of the product exceed the actual price paid for the product. Some states do not allow the exclusion or limitation of incidental or consequential damages. If such laws apply, the limitations or exclusions contained in this statement may not apply to you.

©2021 Rocstorage, Inc. All rights reserved. Rocstor is registered trademark of Rocstorage, Inc. Apple®, the Apple logo, Mac®, MacBook®, MacBook Pro®, MacBook Air®, iPad®, iPad Air®, iPad mini®, iPad Air®, iPhone®, MacOS® are registered trademarks of Apple, Inc. Google® and Chromebook™ are registered trademarks of Google, LLC. Microsoft® is registered trademarks of Microsoft corporation. All other product names and logos mentioned herein may be trademarks of their respective companies. USB Type-C® and USB-C® are registered trademark of USB Implementers Forum. Feature and specification are subject to change without notice. All trademarks and registered trademarks are the property of their respective. All rights reserved.

