

Gas Range, 30", 5 Burners, LPG

Series 7 | Professional

Stainless Steel | LPG



Professional style and performance, with high power burners delivering high heat or the most gentle simmer.

- Top burner heat of 17,000 BTU, for seriously fast boiling
- Convection oven with 4.6 cu ft total capacity
- Non-tip full-extension shelves in main cavity for safe removal of hot dishes
- Made from quality materials and real stainless steel

DIMENSIONS

Height	35 3/4 - 36 3/4"
Width	29 7/8"
Depth	29 1/8"

FEATURES & BENEFITS

Cooktop power

Sealed Dual Flow Burners™ deliver cooktop power up to 17,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Cooking flexibility

<>

Design quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, the Range is built to last.

Easy to clean

<>

Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

Accessories

Square handle option	AH-R30
----------------------	--------

Burner ratings

Maximum burner power	17000 BTU
----------------------	-----------

Power back left	11500BTU
Power back right	11500BTU
Power centre	17000BTU
Power front left	15000BTU
Power front right	15000BTU
Total cooktop power	70000 BTU

Capacity

Shelf positions	5
Shelf positions	5

Cleaning

Easy clean porcelain basepan	•
------------------------------	---

Controls

Electric circuit	3 wire
Metal illuminated dials	•

Gas Requirements

Fitting and pipe	½ NPT, min. ⅝" flex line
Supply Pressure (LPG)	11" to 14" W.C

Oven features

Broil pan	•
Electronic oven control	•
Full extension telescopic	•
Infrared Broiler	•
Internal light	•
Titanium coated, illuminated	•



Oven functions

Bake	•
Broil	•
Convection bake	•
Number of functions	4
Slow cook	•

Oven performance

Bake power	21,500 BTU
Broil power	19,000 BTU

Power requirements

Amperage	15A
Rated current	15A
Supply frequency	60Hz

Product dimensions

Depth	29 1/8"
Height	35 3/4 - 36 3/4"
Width	29 7/8"

Rangetop features

Sealed Dual Flow Burners™	5
Sealed range top	•
Vent trim included	•

Recommended Back Guards Ventilation

Combustible situation	BGRV3-3030H
Non combustible situation	BGRV2-3030 / BGRV2-1230

Recommended hood

HCB30-6_N (Professional)

Safety

ADA compliant	•
Full extension telescopic	•

SKU

82007

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

- [↓](#) User Guide
- [↓](#) Service & Warranty
- [↓](#) Installation Guide

**A PEACE OF MIND SALE****24 Hours 7 Days a Week Customer Support****T 1.888.936.7872 W www.fisherpaykel.com**