



LED Battery work light

with 2x spotlights, 360° rotatable

The rechargeable LED work light from SCHWAIGER® provides the right lighting in every situation with its powerful COB (chip-on-board) LED spotlight and the bright LED headlight. Thanks to the robust, IP43-certified construction, the lamp is very well protected against splash water and is ideal for all kinds

of work. The magnetic base, which can be rotated by 90° on both sides, and the tiltable hook always ensure that the lamp is held securely. On top of that, the battery-operated lamp can be rotated completely through 360° for individual illumination.



ARTICLE INFORMATION

Article Nr
EAN

WLED0080
4004005039818



Last updated: 06.07.2022





FEATURES (WLED0080)

- 3 modes adjustable:
 - > > COB LED (main light) 100% on
 - > > COB LED (main light) 30% on
 - > > LED (headlights) on
- Magnetic base can be rotated 90° on both sides, the lamp is 360° rotatable for an individual alignment of the light
- With battery level indicator on the backside
- ideal illumination due to extremely powerful COB (Chip-on-Board) LED
- built-in lithium battery for mobile power supply
- tiltable hook for hanging the lamp
- rugged and impact-resistant ABS housing
- light and compact design
- 2 LED spotlights with large beam angle
- standable and hangable for hands-free working
- Protection class IP43 (protection against foreign bodies > 1 mm & splash-proof)
- Scope of delivery: LED work light, Micro USB charging cable, instruction manual

TECHNICAL DATA

Connections	1x USB 2.0 Micro-B jack
Power supply	5 VDC , 600 mA
Capacity of battery	1200 mAh
Battery type	lithium polymer (rechargeable)
Type of lamps	5 W COB LED 1 W LED
Luminous flux	350 Lm (main light 100%) 110 Lm (main light 30%) 80 Lm (head light)
Dimmable	yes
Charging time	approx. 3 h
Lifetime (LED)	50000 h

Run time	(main light 100%) 4 h (main light 30%) 6.5 h (head light) 7 h
Protection class	IP43
Material of product	ABS polycarbonate
Colour	black/yellow
Weight (set)	108 g
Dimensions (width)	42 mm
Dimensions (height)	154 mm
Dimensions (depth)	31 mm
Packaging	carton

