



LED-803HD

This adaptable small screen LED backlit monitor is ideal for use in security surveillance and professional AV environments where space can be limited and continuous use is often required.

Benefits

- LED backlight: brighter picture using less power
- Anti-glare coating provides enhanced display
- Always-on capability when power is applied
- Multiple source connections
- Built-in speakers
- Durable metal case
- Remote control for easy access

Accessories

- DC-1500: Factory approved car cord
- HM-401: Under-cabinet hinge mount
- WM-32: Wall mount bracket (fixed/tilting)
- WM-302: Wall mount with 4-way adjustable swing arm

Related Products

LED-803HD2

Specifications

Mount	Free-standing; ¼ - 20 pad top/bottom; VESA 75x75mm
HD Compatible	Yes
Anti-Glare Coating	Yes
Case	Metal
IR Remote Control	Yes
Native Aspect Ratio	4:3
Visible Screen Size	6.4" x 4.8" / 162 x 121.5mm
Resolution	800(H) x 600(V); displays up to 1080p
Brightness Rating	250 cd/m ² (Nit)
Contrast Ratio	500:1
Back Light	LED (20K)
PC Compatibility	Yes
Dot Pitch	0.0675(H) x 0.2025(V) mm
Color Depth	16.7M
Number of Pixels	480,000
Response Time	25ms (Rising/Falling)
Audio Power/Speakers	x2 1.5 Watts
Viewing Angle	70/70/50/70 degrees
HDMI	x2 Inputs
Composite	x1 BNC Input / Output
PC	x1 15-pin D-sub Input
RS-232	x1 3.5mm Input
Audio	x2 RCA Inputs; x1 3.5mm PC Input
Power	x2 2.1mm DC Inputs
Power Requirements	11.5~13 VDC, 1.2A
Power Consumption	10 Watts (Max)
Operating Temperature	32 ~ 122°F / -20 ~ 80°C
Humidity	10% ~ 90% RH (Max)
Dimensions	8.8" x 6.9" x 1.9" / 223 x 176.2 x 47mm
Weight	Net: 2.9 lbs / 1.3 kg

Specifications subject to change.