



INSTALLATION & MAINTENANCE MANUAL

**JB007 / JB007BK / JB008 / JB008BK / JB009
JB009BK / JB0010 / JB0010BK**



GENERAL INSTRUCTIONS

These instructions should be read carefully and retained after installation by the end user for future reference and maintenance.

**These instructions should be used to aid installation of the following products:
JB007 / JB007BK / JB008 / JB008BK / JB009 / JB009BK / JB0010 / JB0010BK**

SAFETY

- This product must be installed in accordance with the latest edition of the IEE Wiring Regulations (BS7671) and current Building Regulations. If in any doubt, consult a qualified electrician
- Please isolate mains prior to installation or maintenance
- Please note the IP (Ingress Protection) rating of this product when deciding the location for installation
- Do not overload this accessory or subject it to conditions outside its rating
- This product is IP66 rated

INSTALLATION

- Provide power to the required point of installation (refer to BS7671 for correct cabling methods)
- Remove the lid of the junction box
- Drill out one or more of the 20mm drilling guides and remove any excess material from around the edge of the hole to ensure a smooth surface



- Install suitable IP rated cable glands (not included) as required
- Drill the fixing holes in the rear of the box. Mark the location of the fixing holes and drill ensuring not to infringe with any gas/water pipes or electrical cables
- Secure the box to the mounting surface and fit the screw caps provided
- Feed the mains cables through the cable glands and tighten to ensure a good seal
- Connect cables as required using suitable connectors (not included)
- Ensuring the gasket does not become damaged or pinched, refit the lid and secure with the screws provided – the screws must be tight to ensure a good seal but do not overtighten

GENERAL

This product should be recycled in the correct manner when it reaches the end of its life. Check local authorities for where facilities exist.

Clean the external surfaces with a damp cloth using a mild solution of detergent and warm water only, do not use aggressive cleaning products or solvents which may damage the product.

Do not use any source of high-pressure washers to maintain or clean this product.



WARRANTY

This product has a warranty of 1 year from date of purchase. Failure to install this product in accordance with the current edition of the IEE Wiring Regulations (BS7671), improper use, or removal of the batch code will invalidate the warranty. If this product should fail within its warranty period, it should be returned to the place of purchase for a free of charge replacement. ML Accessories does not accept responsibility for any installation costs associated with the replacement product. Your statutory rights are not affected. ML Accessories reserve the right to alter product specification without prior notice.



ML Accessories Limited LU5 4LT
www.mlaccessories.co.uk

DCJUN20_V1

