

Unique™ 4" Round Deep Reflector for Koto™ Module

One Piece die-cast trims with Twist-&-Lock system for easy installation



Features

- Convenient Twist-&-Lock design for ease of installation.
- Diecast construction for lasting quality.
- 5" O.D. - 3 7/8" I.D. - 1 3/4" H
- 35° Adjustability

Specifications



Wet Location UL Listed

Technical Details

Construction: Diecast aluminum with a powder coated finish.

Installation: Twist-lock design allows for easy mounting onto the Koto™ LED Module. Clips securely mount trim into the housing and keeps ring flush with ceiling.

Lamp: Koto™ LED Module.



Dimensions:

Options



All White



All Bronze

Product Number

Item	Finish
ELK4717W	All White

Product Number Builder Example: ELK4717W

Unique™ 4" Round Deep Reflector	Finish
ELK4717	
	W All White BZ All Bronze

Compatible Products

For use with Koto™ System 4" Trims



Koto™ Commercial Construction LED Light Engine



ELK19 ELK21
Koto™ LED Light Engine

PRODUCT NUMBER BUILDER

Koto™ LED Light Engine	Lumens	Color Temperature	Beam Angle
ELK			
	19 850 lm	27D 2700K	(blank) 38° lens (Standard)
	21 1100 lm	30D 3000K	-S 18° lens
		35D 3500K	-N 25° lens
		40D 4000K	-W 60° lens
		SDD Sunset Dimming	

ACCESSORIES



Lens
EP731C 18° Lens
EP732C 25° Lens
EP734C 60° Lens



Reflectors
EP735C 15°
EP736C 25°
EP737C 38°
EP738C 60°



Hex Louver
L45
For a better glare shield



Linear Louver
L46
For a wide rectangular illumination pattern



Spread Louver
L47
For a symmetrical broadening of light beams



Clear Lens
L48
Protective clear glass lens

4" Commercial Construction Koto™ Dedicated LED ICA Housings



2-Hour Fire Rated
4" ICA Housing - 7 1/2" Height
New Construction



4" ICA Shallow Maximum
Adjustability Housing - 4" Height
New Construction



4" ICA Housing - 5 1/2" Height
New Construction

CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS
ELK49FICA	120V - Triac/ELV	E4LK98ICA	120V - Triac/ELV	E4LK87ICA	120V - Triac/ELV
ELK49FICAD	120/277V - 0-10V/Triac/ELV	E4LK99ICAD	120/277V - 0-10V/Triac/ELV	E4LK87ICA-EM1	120V - Triac/ELV Emergency Battery Back-up (90 min)
				E4LK88ICAD	120/277V - 0-10V/ Triac/ELV
				E4LK88ICAD-EM1	120/277V - 0-10V/ Triac/ELV Emergency Battery Back-up (90 minute)



4" ICA Housing - 5 1/2" Height
Remodel

CAT NO.	SPECIFICATIONS
E4LK87RICA	120V - Triac/ELV
E4LK88RICAD	120/277V - 0-10V/Triac/ELV