

interphone
cellularline

F3MC



USER MANUAL

Index:

1. Introduction	4
2. Getting started	6
3. Settings	9
4. Intercom	11
5. Phone / GPS	14
6. Music Streaming	17

1 – Introduction

1.1 Hello!

Thank you for choosing our product. InterphoneF3MC is a Bluetooth® helmet headset for wireless entertainment and communication system between rider and passenger. InterphoneF3MC can be installed on most helmets by attachment / detachment quick bracket. The ergonomic shape of the unit is user-friendly also with motorbike gloves. InterphoneF3MC is waterproof tested, up to IP67 protection degree (using the sealant provided).

1.2 Main features

- Intercom:** InterphoneF3MC allows Bluetooth Intercom communication between rider and passenger.
- Phone:** InterphoneF3MC has a Multipoint Bluetooth® connection for dual mobile phone or other Bluetooth devices (mobile phone/GPS navigation).
- Music:** InterphoneF3MC is able to play music from a Bluetooth® device, supporting A2DP and AVRCP profiles (smartphones, MP3 player etc.).
- Vocal guide:** InterphoneF3MC is equipped with a Text To Speech vocal guidance system, that helps the user to operate each product feature and menu.

1.3 Box contents




Pic.1

- A. Bluetooth® unit
- B. Microphone for full face helmet
- C. Microphone for Jet/flip up helmet
- D. Left speaker
- E. Right speaker
- F. Velcro set for speaker/mic + spare POP wind protection
- G. Fixing plates + screwdriver
- H. USB charging cable
- I. USB data cable
- J. Quick guide

Please refer to quick guide for installing F3MC on your helmet, provided in the box (can be also downloaded from Interphone website), otherwise you can also check video TUTORIAL on website www.interphone.com.

2 – Getting Started



Pic.2

- (1) MFB button
- (2) UP button
- (3) DOWN button
- (4) Volume + button
- (5) Volume - button
- (6) Blue led
- (7) Red/Green/Orange led
- (8) Connector

2.1 Main Commands (Pic.2)

Power on	Press MFB button (1), led (6) flashes.
Power off	Press and hold MFB button (1) until you hear “Interphone powering down” message. Led (7) flashes red for few seconds.
Volume	Press buttons (4) to increase or (5) to decrease.
Mute	Press button (5) for about 2 seconds.
Menu	Press buttons (2) or (3) to scroll the menu items. Press MFB button (1) to select an item. Once selected a menu item, you come back to “INTERCOM” menu (Standby) with a short press of MFB button.

2.2 Status led (Pic.2)

Standby	BLUE led (6) flashes every 3 seconds.
Intercom active	BLUE led (6) is solid .
Interphone connected with mobile/GPS	BLUE led (6) flashes twice every 3 seconds.
Pairing mode	BLUE (6) and RED (7) led flash alternately.
Charging	ORANGE led (7) is solid. When charging is completed led (7) becomes solid GREEN.
Battery low	Led (7) is solid RED.

2.3 First Switch on (only twin pack)

Press MFB (1) button to turn on both units. The units are already factory-paired, wait for your language and press MFB (1) button to confirm.
Later two units will be in "INTERCOM" Standby status (Chapter 4).

2.4 First Switch on (only single pack)

Press MFB (1) button to turn on unit, wait for your language and press MFB (1) button to confirm.

Unit will be in "INTERCOM" Standby status (Chapter 4).

The unit will enter in "PAIRING MODE", choose one of these:

- Short press of MFB (1) button – pairing with mobile phone or GPS navigator.
- Short press of Up (2) button – intercom pairing with INTERPHONE device.
- Short press of DOWN (3) button – intercom pairing with other brand device(NON INTERPHONE) ANYCOM mode.
- Long press of MFB (1) until the beep – to cancel "PAIRING MODE". Unit will enter in "INTERCOM" Standby status(Chapter 4) and Blue led (6) will flash every 3 seconds.

2.5 Language selection (after first switch on):

F3MC in Standby mode (Blue led(6) flashing), press UP button(2) and then MFB button(1) to enter in "SETUP" menu. Press again UP button(2), "LANGUAGE SELECTION" start, wait for your language and then press MFB button (1) to confirm it.

If you select a wrong language, follow the steps below:



1. Turn off the F3MC. (Press the MFB for 5s, or until the led lights RED).
2. Turn on the F3MC (Press the MFB for 2s).
3. Short press UP button (2).
4. Short press MFB button (1).
5. Short press UP button (2).
6. Press MFB when you hear your language.

2.6 Audio priorities

F3MC determinates the audio source priority in the following way:

1. Mobile phone
2. Intercom
3. A2DP audio (Smartphone/Player MP3)


F3MC automatically manage priority when audio sources play simultaneously, using the sequence above.

Example:

- Incoming mobile call interrupt ongoing A2DP music.
- Incoming Intercom call does not interrupt an ongoing mobile phone call; the rider, who started the intercom call, will hear a "connection failed" message.

3 – Settings

You can easily customize your F3MC . From Standby mode (Blue led (6) flashing), press UP button (2) and after MFB button (1) to active “SETUP” menu, entering in the main functions Pic.3.



Pic.3

3.1 System settings

Once in “SETUP” menu, scroll items by UP (2) and DOWN (3) button until you find the one you want.

Press MFB (1) button until the beep to change setting or enable a function.

- **Call ID:** when you receive a phone call, F3MC pronounce the name of the caller. It is possible **enable/disable** the function.
- **AUTOMATIC VOLUME: (FULLFACE HELMET/JET HELMET/OFF):** F3MC can adjust volume automatically according as helmet you are using. The user can completely disable the function and adjust the volume manually. **AUTOMATIC VOLUME CONTROL OFF** allows to gain maximum.
- **VOICE ANSWER:** user can answer to a phone call just speaking a voice command. It is possible **enable/disable** the function.
- **ERASE PAIRINGS:** this function allows to cancel all devices paired before from F3MC memory. At the first restart F3MC will enter in pairing mode automatically as explained in Chapter 2.4.
- **VOCAL HELPS:** F3MC has two different levels for vocal helps: **FULL** for unskilled user and **LIMITED** for skilled user. It is possible to choose one of these two options.
- **ANYCOM SEARCH:** active search for other brand's Bluetooth® headsets.
- **INTERCOM SEARCH:** active search for INTERPHONE branded devices.
- **PAIRING MODE:** active search for Bluetooth® devices such as mobile phone, GPS navigator, MP3 player etc.
- **LANGUAGE SELECTION:** active the selection of languages. Wait when you hear your language and then press MFB (1) button to confirm it.

4 – Intercom

F3MC allows intercom communication (INTERCOM) in full duplex between rider and passenger.

4.1 Pairing

Before starting the communication between headsets, is necessary to pair together the units. This process has to be done only one time. F3MC will automatically recognize devices previously paired.

F3MC is compatible with all range of INTERPHONE device (also previous series) and by ANYCOM function is also compatible with other brands of helmet Bluetooth headsets.

Each F3MC can be paired to only one more unit.



If a F3MC unit has been paired with a unit, running a further pairing, with another unit, will delete the pairing with first one.

4.1.1 Pairing with an INTERPHONE MC unit

With both units in Standby mode (led BLUE (6) flashing):

1. On your F3MC unit press once the UP (2) button and then press once the MFB (1) button to activate the “SETUP” menu.
2. Press three times the UP (2) button to select “INTERCOM DEVICE SEARCH” feature, press the MFB (1) until the beep to start the search.
3. On the other unit F3MC press UP (2) button and then press once MFB (1) button to activate the “SETUP” menu.
4. Press UP (2) button two times, the second MC unit will go in “PAIRING MODE”.
5. After few seconds the units will be paired, intercom connection will be automatically started (led BLUE (6) on). To stop the intercom communication press once MFB (1) button on one of the two units.

4.1.2 Pairing with an INTERPHONE unit (**not MC**).

With your unit in Standby mode (led BLUE (6) flashing):

1. Press once the UP (2) button and then press once the MFB (1) button to activate the “SETUP” menu.
2. Press three times the UP (2) button to select “INTERCOM DEVICE SEARCH” feature, press the MFB (1) until the beep to start the search.
3. On the second Interphone unit (previous series not “MC”), with unit off, push and keep pressed the MFB button until the alternate flashing red/blue of unit led.
4. After few seconds the units will be paired, intercom connection will be automatically started (led BLUE (6) on). To stop the intercom communication press once MFB (1) button on one of the two units.

4.1.3 Pairing with units not Interphone (other brands)


With your unit in Standby mode (led BLUE (6) flashing):

1. Press once the UP (2) button and then press once the MFB (1) button to activate the “SETUP” menu.
2. Press four times the UP (2) button to select “ANYCOM SEARCH” feature, press the MFB (1) until the beep to start the search.
3. On the second unit **NOT** Interphone start the “phone search/phone pairing mode”, see user manual of NOT Interphone unit for more details.
4. After few seconds the units will be paired, intercom connection will be automatically started (led BLUE (6) on). To stop the intercom communication press once MFB (1) button on your F3MC unit.

4.2 Intercom communication between two units (from “INTERCOM” menu)

To start an intercom communication between your F3MC (unit nr1 Pic. 4) and another one (unit nr2 Pic. 4) follow these steps:

1. Pair units 1 and 2 (chapters 4.1.1/4.1.2/4.1.3), this is necessary only once.
2. With your F3MC unit in Standby mode (led BLUE (6) flashing), press once the MFB (1) button, connection will be started. The vocal guidance will prompt a message for intercom activation, BLUE (6) led of F3MC units will lights up. To stop the intercom communication press once MFB (1) button on your F3MC, both units will go in Standby mode.



Pic.4

4.3 Intercom tips

Once activated the intercom channel, communication remains active until it is manually stopped by the rider. It is suggested to suspend the intercom conversation, if not necessary, to optimize battery life.

If F3MC is paired with an other unit, it allows to connect only one Bluetooth® devices (phones, GPS, etc..).

“INTERCOM” audio quality is strongly influenced by:

- proper installation of speakers and microphone inside the helmet. Always check very carefully that speakers are placed exactly on your ears, and microphone is placed as close as possible to your mouth. Any error on these positions will cause an important decrease of performances.
- environment (electromagnetic interference, natural obstacles, etc.).
- aerodynamic protection of your motorcycle.
- type of helmet used.

5 – Phone/GPS

F3MC can be used together with Bluetooth® devices, as mobile phones, GPS devices, MP3 players.

To each F3MC unit is possible to connect, in the same time, max two Bluetooth® devices.

5.1 Pairing

Before using the F3MC unit with these devices, is necessary to run the pairing procedure. This is necessary only once, after F3MC will automatically recognize and connect devices already paired.





Pairing procedure

1. Start Bluetooth® service on mobile phone / GPS / MP3 player (check the device's user guide for more details).
2. With F3MC in Standby mode (led BLUE (6) flashing), press UP (2) button and then press MFB (1) button to activate “SETUP” menu. Press UP (2) button twice, F3MC will enter in “PAIRING MODE” .
3. Start searching for new Bluetooth® devices on mobile phone / GPS / MP3 player.
4. After few moments the device in searching mode will list “Interphone F3MC”. Select it.
5. If prompted for a PIN number, type “0000” (four times the zero number).
6. F3MC vocal guide will confirm the successful pairing with the message “PAIRING SUCCESSFUL, CONNECTED TO PHONE”. F3MC will go in Standby mode, the led BLUE (6) will flash twice, every three seconds.
7. If the Bluetooth® device ask authorization to phonebook access, confirm.

If you want to pair a second device, repeat the pairing procedure from step 1).

5.2 Incoming phone calls

As indicated in chapter 2.6, phone calls have the highest priority and will override each of other F3MC feature. During an incoming phone call these are the possible commands:

Answer to a phone call		Push MFB (1) or pronounce loudly any word (in case that voice answer feature is enabled Chapter 3.1).
End a phone call		Push once the MFB (1) button.
Reject a phone call		Push DOWN (3) button to reject. Otherwise wait for 15 seconds, the call will be automatically rejected.
Ringtone muting		Push UP (2) button to mute the ringtone.

5.3 Phone

All features related to phone can be activated entering into “PHONE” menu of F3MC. With F3MC in Standby mode (led BLUE (6) flashing), push DOWN (3) button one time and then press the MFB (1) button to activate the “PHONE” menu.

Redialling last number		Press UP(2) button to redial last number.
Voice dial		Press DOWN(3) button to activate the voice dial feature of the phone. Follow phone's prompts to complete the task.

5.4 Phone tips

If two different phones are connected at the same time to a single F3MC unit, the features “**Redialling last number**” e “**Voice dial**” can be used only with the FIRST connected phone. The second connected phone can only receive calls, or managed by hand commands directly on the phone.

Depending on the phone model it could be necessary to have an active internet connection to use the “**Voice dial**” feature.

The “**Voice dial**” feature could not be supported by your phone. Check the phone user manual for more details.

From “SETUP” menu is possible to change two settings for the phone usage (Caller ID ON/OFF e Voice answer ON/OFF), see chapter 3.1 for more details.

From “PHONE” menu, it is possible to go in Standby mode (led BLUE (6) flashing-menu “INTERCOM”), pressing once the MFB (1) button.

5.5 GPS

After completing the pairing between F3MC and GPS device (see chapter 5.1) is possible to listen to vocal instructions from the GPS for the routing. The GPS will stop any intercom communication each time that will send a vocal instruction.



Check that the GPS device is compatible with Bluetooth® headsets, “HFP” Bluetooth® profile has to be supported by GPS. Check GPS user guide for more details. F3MC uses the “HFP” Bluetooth® profile to manage the connection with GPS devices.

Navigation apps, installed on smartphone devices, use the A2DP Bluetooth® profile to send routing indications to headset. This profile doesn't let to automatically stop the intercom communication when needed.



Car GPS navigator usually don't support the HFP Bluetooth® profile. For this reason these devices can't send vocal routing instructions to Bluetooth® headset. Check GPS user guide for more details.

6 – Music streaming

With F3MC is possible to listen to music from an A2DP Bluetooth® device (smartphone, MP3 player, etc..). To play music from these devices is necessary to pair the F3MC unit with the music source device (Chapter 5.1).

6.1 Music play



With F3MC in Standby mode (led BLUE (6) flashing), push DOWN button for three times and then press the MFB (1) button to activate the “MUSIC STREAMING” menu.

Play/Pause		Push the MFB (1) button until the beep to play/pause the music.
Track select		Press UP (2) or DOWN (3) button to select the previous or the next track.



During the music listening, it is possible to go in Standby mode (led BLUE (6) flashing-menu “INTERCOM”), pressing the MFB (1) button. To resume the music listening it will be necessary to go again into “MUSIC” menu, as described at beginning of this chapter.

6.2 Song sharing

F3MC is equipped with the “SONG SHARING” feature, to share the music streaming among two Interphone MC units.

Start/Stop sharing		Press UP (2) button until the beep to start/stop the song sharing with Interphone “A” (unit nr.2 chapter 4.3 - Pic.4)
		Press DOWN (3) button until the beep to start/stop the song sharing with Interphone “B” (unit nr.2 chapter 4.3 - Pic.5)

During the sharing is possible to start an **intercom session**, as indicated in the following table.


On MC unit that is sharing the music		Press the MFB (1) button to activate the INTERCOM menu. Press again the MFB (1) button to start an intercom call.
On MC unit that is receiving the music		Press the MFB (1) button to start an intercom call.

6.3 Important informations for “MUSIC STREAMING” feature

- Only Bluetooth® devices supporting A2DP profile can stream stereo music to F3MC.
- Only Bluetooth® devices supporting AVRCP can be managed by F3MC.
- The song sharing feature couldn't be used to share other audio sources, like GPS, Phone calls or intercom calls.
- The song sharing feature is optimized to work with Interphone devices of MC range. Using this feature, with other device, could bring a decrease of listening quality on the headset unit, that will receive the music shared.
- The listening audio quality is strictly connected to the quality of music source (bitrate and codec type of audio file, quality of Bluetooth® player, etc.).

Appendix 1

Menu chart.



Important information

IMPORTANT INFORMATION ON THE PRODUCT BATTERY

Do not store the device without charging it. Failure to do so may irreversibly damage the capacity of the battery. Recharge the battery completely every TWO months.

IMPORTANT INFORMATION ON PRODUCT WATERPROOFING

The external unit (control unit), mated to the connector on the audio kit, is classified IP67 as per the IEC60529 standard, when used with the sealer provided in the package. Therefore, the control unit, when mated to the connector on the audio kit, may be submerged in a meter of freshwater for a maximum of 30 (thirty) minutes.

Despite this classification, the device is not immune to greater stresses, such as prolonged immersion or high-pressure jets of water.

Using the device in conditions of bad weather, at high speeds, may be equivalent to subjecting it to a high-pressure jet of water.

FOLLOW THESE SUGGESTIONS CAREFULLY TO PREVENT DAMAGE TO THE DEVICE:

Do not immerse the device in freshwater over one metre deep for more than 30 minutes.

Do not store the device when it is wet: dry it with a clean, soft cloth. Dry any water or moisture in the control unit connector and/or the audio kit connector by applying warm air for at least 10 minutes. This will keep the contacts from corroding.

Keep the device away from salt water, ionised water, beverages and other liquids. If the device is exposed to liquids other than freshwater, wash it with cold, freshwater and dry it carefully with a clean, soft cloth.

Keep the device away from high-pressure jets of water.

Be sure to reapply the sealer supplied in the package if the sealer disappears when the device is used for a prolonged period of time.

Be sure the connector on the audio kit is inserted into the control unit completely. Otherwise, complete protection against water and dust is not guaranteed.

Technical Specifications			
Bluetooth® compliance:	Bluetooth® V.3.0 - Class II		
Supported Bluetooth® profiles:	HFP	A2DP	AVRCP
Dimensions mm:	60x80x30		
Weight:	44g		
Range:	Up to 10 metres		
Talk time:	12h		
Stand-by time:	700h		
Charging time:	3h		
Battery type:	Rechargeable Li-ion		



EQUIPMENT DISPOSAL INSTRUCTIONS FOR DOMESTIC USERS

(Applicable within the European Union and those countries with separate collection systems)

The marking shown on the product or its literature indicates that at the end of its life the product should not be disposed together with other household waste. To prevent possible harm to the environment or human health from uncontrolled waste disposal, please separate this from other types of wastes and recycle it responsibly to promote the sustainable reuse of material resources.

Domestic users are invited to contact the sales point where the product was purchased or the local office with information regarding recycling of this type of product. Business users should contact their supplier and check the terms and conditions of the purchase contract. This product should not be mixed with other commercial waste for disposal purposes.

This product has an embedded, non-replaceable battery, do not attempt to open the product or remove the battery as this may cause injury and damage the product. When disposing of the product, please contact your local waste disposal service in order to remove the battery. The battery contained within the device and been designed to be used throughout the life cycle of the product.

CE 0560

This product is CE marked in accordance with the provisions of the R&TTE Directive (1999/5/EC) and the RoHS Directive (2011/65/EU). With this CE mark Cellular Italy S.p.A. declares that this product complies with the essential requirements and other relevant provisions of the 1999/5/EC and 2011/65/EU Directives. The user is forbidden to make changes or modifications of any kind to this device. Changes or modifications not expressly approved by Cellular Italy S.p.A. will void the user's authorisation to operate the device. Bluetooth® is a trademark owned by Bluetooth SIG, Inc. For more information please visit the website: www.interphone.com