

DIGI 18, LTE 700, Ch 21-48 (Color box)

Art. Number 105480



TRIAx UHF LTE 700 Aerials

Disruption free installation from rooftop to outlet.

- Interference protection from LTE 700 & 800 signals
- Quick and easy installation with semi-assembled aerials
- Mechanical filtering for higher gain
- Reliable high-quality aerials secures end-consumer satisfaction
- Corrosion and weather proof dipole housing
- Designed to receive DTT signals in the 470...694 MHz range
- Access to reliable, expert support from TRIAX

Technical Specifications

ORDER INFORMATION

EAN Number 5702661054808

FREQUENCY RANGE

Band UHF
Channels 21...48
Frequency range UHF | MHz 470...694 MHz
LTE protection @ 700Mhz

GAIN

Gain | dBi 14 max dBi
Gain @ 474 MHz (Ch. 21) | dBi 11.3 dBi

LOSS

Rejection @ 788 MHz (Ch. 60) | dB 8.9 dB

ELECTRICAL

Front to back ratio - horizontal | dB 25 dB

MECHANICAL



TRIAx

connecting the future

Technical Specifications

Elements	17
Windload @42 m/s N	59 N
Beamwidth horizontal °	±25 °
Bracketry	Mast bracket - rear
Main material	Aluminium
Packing QTY	1
Product Length mm	1414 mm
Product Width mm	480 mm
Packaging Height m	0.080 m
Packaging Width m	0.230 m
Packaging Depth m	0.765 m
Packaging Volume m3	0.014 m3
Net Weight kg	1.250 kg
Tara Weight kg	0.350 kg
Total Weight kg	1.600 kg

