


Unless otherwise specified upon order, Customer
Required Clearance is automatically set to 2 mm by
Pulseroller USA Order Entry System

INCLUDED ITEMS		
ITEM	DESCRIPTION	QTY
1		0
2	PR-D-30H-XX-(XX) MOTOR SHAFT FIXING BRACKET - SPECIFY AT TIME OF ORDER	1

PR-AD-48-xxx-xxZxFQ		
TUBE DIA	48.6 mm	
INTERLOCK	ROUND GROOVE PULLEY	
MOTOR END	NON THREADED HEX SHAFT	
IDLER END	SPRING LOADED HEX	
CONNECTOR	JST (S) OR M8 (M)	

xxx = RL in mm
xx = Speed Code



E	24-JAN-2023	COMBINED JST & AI TO SAME DWG. UPDATED DWG NUMBER		THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL, IS SUBMITTED IN CONFIDENCE, AND IS PROPRIETARY INFORMATION OF PULSEROLLER AND SHALL BE USED ONLY IN CONJUNCTION WITH AND PERFORMANCE OF THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT PULSEROLLER PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS.	DATE: 21-MAR-2014	TITLE: STANDARD 48 DIA ROUND GROOVE PULLEY PART NUMBER PR-AD-48-xxx-xxZxFQ
B	15-DEC-2020	ADDED CUSTOMER REQUIRED CLEARANCE			DESIGNED BY:	FOR: SENERGY MOTOR ROLLER PULSEROLLER STANDARDS
C	10-MAY-2021	CORRECTED LENGTH FORMULA			CHECKED BY:	
D	06-JUL-2021	ADDED DESCRIPTION CHART AND FIXING BRACKET			SCALE: NONE	
REV.	DATE	DESCRIPTION	✓		SHEET: 1 OF 1	DWG. NO: PR-AD-48-xxx-xxZxFQ REV: E