

floor grommets

access / power and data



EG0010



EG0030



EG0040



EG0045



Dimensions and technical information **p. 37**

Pack	Cat. Nos.	Plastic access grommets	Pack	Cat. Nos.	Plastic power and data grommets
1	EG0010	144 mm Ø – cut-out size 127 mm Ø Quick fit installation Precision engineered from hard wearing durable ABS Grey mouldings. Other colours available to special order Conform to BS EN 61534-22 Simply secured by pushing down the spring-loaded screws and rotating a quarter turn Recommended for use in light traffic areas Avoid positioning in walkways or under static loads Can accomodate all cable types or three metal conduits up to a 20 mm Ø or 25 mm without foam	1	EG0040	169 mm Ø – cut-out size 152 mm Ø Quick fit installation Precision engineered from hard wearing durable ABS Grey mouldings. Other colours available to special order. Conform to BS EN 61534-22 Removable carpet recess Cable flap feature so grommet lid can be closed while in use Simply secured by pushing down the spring-loaded screws and rotating a quarter turn Recommended for use in light traffic areas Avoid positioning in walkways or under static loads For information on knockout sizes p. 37 13 A power grommet Supplied complete with 13 A unswitched socket
1	EG0030	169 mm Ø – cut-out size 152 mm Ø Allows power, data and flexible conduit up to 32 mm to pass through raised access floor Lid can be locked with screw (included) Maximum number of conduits : 9 x 20 mm Ø 5 x 25 mm Ø 3 x 32 mm Ø	1	EG0045	RCD 30 mA switched socket power grommet Supplied complete with 13 A RCD 30 mA switched socket passive
1	EG0055	232 mm Ø – cut-out size 215 mm Ø High capacity grommet Recommended for installation in light traffic areas Maximum number of conduits : 18 x 20 mm Ø 10 x 25 mm Ø 6 x 32 mm Ø	1	EG0051	13 A power/data grommet Supplied complete with 13 A socket and 1 x 37 x 22 mm cut-out
		Aluminium access grommet Body – cast aluminium Lid – injection moulded plastic Nylon 66 with neoprene cable gasket Secured by quarter-turn fasteners Floor depth 25 to 55 mm Access grommet depth 60 mm (95 mm when back box included)	1	EG0052	Data grommet Supplied complete with data plate 2 x 37 x 22 mm cut-out No knockout
1	EG0015	144 mm Ø – cut-out size 127 mm Ø Allows power, data and flexible conduit up to 25 mm to pass through raised access floor	1	EG0053	Cleaners floor grommets 169 mm Ø Non-standard 5 A socket
		Aluminium power grommet For information on knockout sizes p. 37	1	EG0035	Single switched socket
1	EG0025	13 A power grommet Supplied complete with 13 A switched socket			Pre-wired power grommets Recommended for use in light traffic areas For information on knockout sizes p. 37 169 mm Ø – cut-out size 152 mm Ø Cleaners socket version DP1332 - 3 m unfused DP1532 - 5 m unfused DP1313 - 3 m 13 A fused DP1513 - 5 m 13 A fused RCD 30 mA switched socket version DP1332 - 3 m unfused DP1532 - 5 m unfused DP1313 - 3 m 13 A fused DP1513 - 5 m 13 A fused



Please consult us for IP 66 assembled fixed or hinged lid grommets with power and data sockets
contact us on +44 (0) 370 608 9020

