

LINK

Assembly Instructions

Tools Required to Fix From Above:

- Pencil
- Drill + drill bits
- 16mm Hole Saw

Sheet Code: BP-IM-074_REV2
Release Date: 08/04/2022

Copyright 2022 Spotspot Ltd. (T/A Bouncepad) all rights reserved. Confidential, no part of this publication may be reproduced or transmitted in any form without the written permission of the copyright holder.






In the Box




Fixings List

* Due to the modular nature of our product range you may receive additional fixings in the fixings kit




1

Remove Front and Back Screw Covers.




2

Remove Faceplate.




3


Remove Cable Lock.




TEXAS POE
GAF-Lightning-PD



REDPARK
Gigabit+PoE Adapter L6-NETPOE



BELKIN
Ethernet + Power




TEXAS POE
GAT-USBC-PD

4


Select your PoE device and note its location in relation to the mounting slots






5

Insert the tie through the cable slots and then clasp over the POE device.




6

Specifically for Texas PoE GAT-USB-PD use velcro pad for attachment




7

Feed the ethernet cable through the cable exit.




8

Connect the ethernet cable to the POE and secure the cable with the cable lock.




A1

Use a pencil to mark pilot hole locations.




A2

Use a drill bit suitable for your surface and make 4x pilot holes




A3

If running a ethernet or USB cable through the surface use a hole saw in the cable exit position.



A4


Secure the Link to the surface with 4x No.8 Self tapping screws. Rawl plugs are provided if required.



9


Connect the USB cable to the tablet, then place inside the enclosure. Re-attach the faceplate.






10

Use 6x M3 Screws to secure faceplate.




11

Reattach the front and back screw covers



12

Set up the video-conferencing software and peripherals as per the provider's instructions.



13

For additional security, tether your Link with a Kensington security cable. *Security cable not provided.