

TC-700

Professional Two-way Radio

Ideal for high-level professionals who want powerful yet streamlined communication tools, the TC-700 series are packed with cutting-edge technology and HYT innovations. HYT's voice compander audio enhancement and a powerful 1W speaker ensure superb clear, crisp sound, even in noisy environments. Its sleek, ergonomic design makes this TC-700 series radio easy to hold and carry - and it's so lightweight you can take it virtually anywhere.

- Wide-band Coverage
- High-quality Audio Output
- Safety Assurance
- HYT HDC2400™ and HDC1200 Signalling



Super Functions

Wide-band Coverage

Allows users the flexibility to select their frequency for use in their respective work environment.

Powerful Audio Output

HYT's voice compander audio enhancement and a powerful 1W speaker (with a diameter of 40mm) ensure superb clear, crisp sound, even in noisy environments.

Safety Assurance

Safety and security are critical factors for modern organizations. The TC-700's Lone worker, Man Down (optional) and Emergency Siren features are designed to assure your safety in case of emergencies or accidents.

Built-in Scrambler

Maintaining private and secure communications is increasingly important, with potentially sensitive information flowing back and forth. The TC-700's Scrambler feature provides enhanced security for your important public safety and private security communications.

Professional Two-way Radio

Whisper

The Whisper feature means that even the quietest message can be transmitted and understood.

Channel Annunciation

The feature enables radio to report the current channel number when power on or switching channel, offering you notable convenience.

HYT HDC2400™ and HDC1200 Signalling

HYT HDC2400™ signaling system allows features including Identification, Calling Timer, Voice Storage, Retrieve Record, Individual Call, Group Call, Broadcast, Stun/Kill & Revive, Status Inquiry, Short Message and Data Transmission. (Some are features of dispatch center.)

Compatible with MDC1200, the HDC1200 Signalling allows functions including PTT ID Encode, Emergency Encode, Radio Check Decode, Stun/Kill & Revive, Individual Call, Group Call, Broadcast, etc.

TC-700



New Functions

Lone Worker

The feature provides added security and safety for individuals who work remotely from their team. Should a user not respond to a regular warning tone, then a defined emergency procedure is activated.

Man Down (optional)

When feature enabled, a defined emergency procedure is activated if the radio is horizontally or inversely positioned for a certain length of time. Place the radio vertically to disable the emergency.

Safety Check

Should the user not respond to a safety check signal from the dispatch center or another authorized radio, then a defined emergency procedure is activated.

Power on Self-Test

The radio itself checks radio status automatically when power on, and emits corresponding alert if an error occurs, allows the user to early detect unit faults.

Embedded Message & Serial Number

The radio's memory can store messages including service and programming records, for remarkable ease of maintenance; the feature also makes a unit identifiable by Serial Number.

Emergency

Press the Emergency key to emit emergency alarm, or send ENI (Emergency Number Identity) / background tone to a pre-defined person or the dispatch center.

Auto Contact

The feature is especially helpful in high-demanding communication environments, such as climbing, exploration, and rescue work. When feature enabled, the radio beeps when the user is moving out of communication range.

Rental

The Rental feature limits the time period that a radio can be rented. The radio will be disabled once the time elapses.

Software upgradeable (optional)

Allows new functions add-in to accommodate future updates.

PC Tuning


Enables remarkable ease of maintenance.

Patrol Record (optional)

Patrol system for real-time (or non-real-time) data transmission consists of the TC-700 radio supporting Patrol Record, patrol transmitter TX-90, control center TM-800, patrol management software, data transmission cable.

Recommended Applications

- Security
- Firefighters
- Public utilities
- Property management
- Construction sites
- Hotel



Accessories

Standard Accessories

UHF / VHF Antenna
Switching Power Adapter (100-240V) PS1009 (different power cords for different countries and areas)
Spring Belt Clip BC08 (compatible with BL1703)
MCU Rapid-rate Charger CH10L07
LI-Ion Battery (1700mAh) BL1703
Strap RO04

Optional Accessories



Li-ion Battery (2100mAh)
BL2102
Ni-MH Battery (1800mAh)
BH1801



MCU Rapid-rate Multi-unit Charger
for Li-ion/Ni-MH Batteries MCA03



Six-unit Switching Power
PS7002
Vehicle Adapter
CHV09



Noise-Cancelling Remote
Speaker Microphone
(350-390MHz) SM13M2


Water Resistant Remote
Speaker Microphone(IP56)
SM13M1



Earbud with in-Line PTT & VOX
ESM11



D-earset with Boom
Microphone & VOX EHM16



Light Weight, Single-Muff
Headset with in-Line PTT & VOX
ECM12

Earbud with on-MIC PTT & VOX
ESM12

D-earset with in-Line
MIC & VOX EHM15



3-Wire Surveillance Earpiece
with Transparent Acoustic Tube
(black/beige) EAM16 / EAM15
Earpiece with on-MIC
PTT & VOX & Transparent
Acoustic Tube EAM12
2-Wire Surveillance Earpiece
with VOX & Transparent
Acoustic Tube (black) EAM13



Light Weight, Throat-Vibrating
Earpiece ELM01
Ear Canal Bone Induction
Earpiece EBM01



Behind-the-Head, Noise-Cancelling
Headset ECM14
Noise-Cancelling Headset
ECM13



Remote Speaker Microphone
SM08M3

Receive-only Earpiece with
Transparent Acoustic Tube
(for use with remote speaker
microphone) ESS08

Receive-only Earbud
(for use with remote speaker
microphone) ESS07



Chest Pack
LCBN13

Leather Carrying Case (swivel)
(thin battery / thick battery)
LCBN41 / LCBN42

Spring Belt Clip BC09(compatible with BH1801&BL2102)
Programming Cable (COM port) PC19
Programming Cable (USB to serial port) PC26



2-wire Earpiece with Wireless
Earphone and Neck Loop
EWM03

Applicable MIL-STD-810C/D/E/F

Applicable MIL-STD	810C Methods Procedures	810D Methods Procedures	810E Methods Procedures	810F Methods Procedures
Low Pressure	500.1 1	500.2 1,2	500.3 1,2	500.4 1
High Temperature	501.1 1,2	501.2 1,2	501.3 1,2	501.4 1,2
Low Temperature	502.1 1	502.2 1,2	502.3 1,2	502.4 1,2
Temp. Shock	503.1 1	503.2 1	503.3 1	503.4 1
Solar Radiation	505.1 1	505.2 1	505.3 1	505.4 1,2
Rain	506.1 2	506.2 2	506.3 1,2	506.4 1,2
Humidity	507.1 2	507.2 2,3	507.3 2,3	507.4 1
Salt Fog	509.1 1	509.2 1	509.3 1	509.4 1
Dust	510.1 1	510.2 1	510.3 1	510.4 1
Vibration	514.2 8,10	514.3 1	514.4 1	514.5 1
Shock	516.2 1,2,5	516.3 1,4	516.4 1,4	516.5 1,4

General

Frequency Range(MHz)	VHF: 136-174 UHF: 350-390 420-470 440-490 400-470
Channel Capacity	16
Channel Spacing(KHz)	25 /20/12.5
Operating Voltage(V)	7.4
Battery	1700mAh (Li-ion)
Battery Life (5-5-90 duty cycle)	About 14 Hours
Frequency Stability(ppm)	± 2.5
Operating Temperature(°C)	-30~+60
Antenna Impedance(Ω)	50
Dimensions(LxWxH)(with battery, without antenna)(mm)	122x55x35
Weight (with antenna & battery)(g)	316

Transmitter

RF Power Output	5W/1W (VHF) 4W/1W (UHF)
Modulation	16KΦ F3E/11KΦ F3E
Spurious and Harmonics	-36dBm<1GHz -30dBm>1GHz
FM Noise	45/40dB
Audio Distortion	≤5%

All Specifications are tested according to TIA/EIA-603, and subject to change without notice due to continuous development.

Receiver

Sensitivity	0.25/0.35 μ V
Selectivity	70/60dB
Intermodulation	65dB
Spurious Response Rejection	70dB
S/N	45/40dB
Rated Audio Power Output	1W
Rated Audio Distortion	≤10%



Hytera Communications Corporation Limited

Address: HYT Tower, Hi-Tech Industrial Park North, Beihuan Rd., Nanshan District, Shenzhen, China

Tel: +86-755-2697 2999 **Fax:** +86-755-8613 7139 **Post:** 518057

Http://www.hytera.com Stock Code: 002583

Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

HYT, Hytera are registered trademarks of Hytera Co., Ltd. © 2012 Hytera Co., Ltd. All Rights Reserved.

Your Local Dealer

