



# Sena WiFi Docking Station Quick Start Guide


ENGLISH



## [WiFi Docking Station]

1

2.0.0




[USB Power and Data Cable]

[World Wide USB Wall Charger]

### Notice:

Please use the USB Power and Data Cable and the World Wide USB Wall Charger included in the package or a compatible third-party microUSB cable (5V and higher than 1A) with the **WiFi Docking Station**. Do not connect the **WiFi Docking Station** to a USB port on your PC.

## LED Description



2

## Charging Status

- Disconnected
- Charging (Main unit is powered off)
- Fully charged

### Note:

- Charging (Main unit is powered on).
- To upgrade the firmware, power off the main unit.

## Firmware Upgrade Status


- Disconnected or no firmware upgrade available
- Upgrading firmware
- Firmware upgrade completed

## WiFi Status

- Disconnected from an WiFi access point
- Searching for WiFi access point
- Connected to an access point

3


## Powering On



- Insert the USB Power and Data Cable into the microUSB Power Port.

## Attaching a Main Unit

Connect the main unit to the microUSB cable and attach it to the **WiFi Docking Station**. Before connecting the main unit, power off the unit.



### Note:

If you leave the main unit on when connecting it, the charging LED on the **WiFi Docking Station** will blink red slowly.

4

## Connection Setup

- Open the **Sena Motorcycles App**.

- Tap the Menu button (⚙️) in the top-right corner of the screen and select **Update via WiFi**.

- Follow the instructions on the **Sena Motorcycles App** to connect the **WiFi Docking Station** to a WiFi access point.

### Note:

- To change the WiFi access point, perform the Factory Reset then repeat the steps above.
- You can download the **Sena Motorcycles App** for Android and Apple operating systems from [www.sena.com](http://www.sena.com).

## Upgrading the Firmware of a Main Unit

The firmware will be upgraded automatically while your main unit is charging. If you want to manually upgrade the firmware, change the setting on the **Sena Motorcycles App**.

### Note:

Do not unplug the USB Power and Data Cable from the **WiFi Docking Station** while upgrading the firmware. The product may be damaged.

5

## Factory Reset

If you want to restore the **WiFi Docking Station** to the factory default settings, you can easily reset the unit:

- Locate the pinhole reset button on the unit.
- Gently insert a paperclip into the hole and tap the **Factory Reset Button** with light pressure.
- The **WiFi Docking Station** will automatically restart with the three LEDs on.



### Note:

The **WiFi Docking Station** will be restored to factory default settings which include the WiFi configuration setup, the firmware setup and the language setup.